

Potable Water Tanks

Capacities from 1,300-10,000 Litres

10 Year
Warranty*



Specifically designed to store water for animal drinking or emergency human consumption, Kingspan potable water tanks are made from WRAS approved material.



V1300WP

Capacity 1300 Ltrs/285 Gals
Outlet 2" BSP male
Dia. 1210 mm
Height 1415 mm



V2500WP

Capacity 2500 Ltrs/550 Gals
Outlet 2" BSP male
Dia. 1635 mm
Height 1450 mm



V3600WP

Capacity 3600 Ltrs/800 Gals
Outlet 2" BSP male
Dia. 1885 mm
Height 1855 mm

All tanks are also available in non potable versions, supplied in grey.

Please quote corresponding codes,
V1300W, V2500W,
V3600W, V5000W,
V10000W



V5000WP

Capacity 5000 ITRS/1100 Gals
Outlet 2" BSP male
Dia. 2035 mm
Height 2265 mm



V10000WP

Capacity 10000 Ltrs/2200 Gals
Outlet 2" BSP male
Dia. 2630 mm
Height 2500 mm

*10 year warranty applies to the tank only

Large Scale Storage Solutions

15,000-litre Liquid Fertiliser, AdBlue® & Water Storage Solutions

Tank
Guarantee*



AgriMaster Liquid Fertiliser



AM15000

Weight: 340 kg

- Can hold up to 1.4 SG liquid fertiliser solution
- Easily monitor liquid fertiliser levels with the tank's semi-transparent design

BlueMaster AdBlue®



BM15000

Weight: 310 kg

- Can hold up to 1.1 SG AdBlue® solution
- AdBlue® level is readily visible to the eye due to the tank's semi-transparent colour

AquaBank Water



AB15000

Weight: 365 kg

The Benefits of Black Colour:

- Algae growth prevention
- Preserves rainwater quality
- Enhanced water heating efficiency

Features & Benefits

- **Superior Construction**
Crafted as a single, seamless unit for ultimate durability.
- **Quality Material**
Engineered from high-quality polyethylene for outstanding strength.
- **Smart Monitoring**
Local or remote level monitoring options are available.
- **Corrosion-Free**
Resists rust and degradation for long-lasting reliability.
- **Maintenance-Free**
No repainting needed, ensuring hassle-free ownership.
- **Weatherproof**
UV stabilised to withstand harsh weather conditions.
- **Easy Transport**
Fits standard trucks for effortless mobility.
- **Simple Installation**
Compatible with farm equipment for easy setup and relocation.

Dimensions

Diameter 3660 mm
Height 2480 mm

Specification

- Access lid 22"
- Inspection lid 8"
- 2" (or optional 3") bottom outlet fitted with stainless steel ball valve
- Ventilation outlet
- 4 Lifting Points
- Moulded in mounting points
- Stainless steel fittings with EPDM rubber gaskets